NSN 5305-01-023-6238

Assembled Washer Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-023-6238 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.218 inches **Fastener Length:** Between 0.280 inches and 0.312 inches **Head Style:** Pan **Head Diameter:** Between 0.256 inches and 0.270 inches **Head Height:** Between 0.087 inches and 0.097 inches Washer Quantity: **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): 32 **Secondary Washer Relationship To Primary Washer:** Not identical **Secondary Washer Style:** Flat **Primary Washer Outside Diameter:** 0.253 inches **Secondary Washer Outside Diameter:** Between 0.253 inches and 0.263 inches **Primary Washer Style:** Split helical ring **Primary Washer Material Thickness:** 0.031 inches **Secondary Washer Material Thickness:** Between 0.013 inches and 0.019 inches Material: Steel comp 430 or steel comp 302 or steel comp 303 or steel comp 301 or steel comp 304 or steel comp 316 or stainless steel **Surface Treatment: Passivate**

Unc

Thread Series Designator:

NSN 5305-01-023-6238

Assembled Washer Screw - Page 2 of 2



Specification Data	a
--------------------	---

80205-nas1301 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0